

**PCT**WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H04B 7/195, 7/19		A2	(11) International Publication Number: WO 95/35602
			(43) International Publication Date: 28 December 1995 (28.12.95)
(21) International Application Number: PCT/US95/07837		(81) Designated States: AM, AT, AU, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LT, LU, LV, MD, MG, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TT, UA, UG, UZ, VN, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG), ARIPO patent (KE, MW, SD, SZ, UG).	
(22) International Filing Date: 21 June 1995 (21.06.95)			
(30) Priority Data: 08/263,835 22 June 1994 (22.06.94) US			
(71) Applicant: ERICSSON INC. [US/US]; One Triangle Drive, P.O. Box 13969, Research Triangle Park, NC 27709 (US).			
(72) Inventor: DENT, Paul, W.; Stehags Prästgård, S-240 36 Stehags (SE).			
(74) Agents: GRUDZIECKI, Ronald, L. et al.; Burns, Doane, Swecker & Mathis, P.O. Box 1404, Alexandria, VA 22313-1404 (US).			
		Published <i>Without international search report and to be republished upon receipt of that report.</i>	


031431 U.S. PTO
10/771862

020304

(54) Title: RADIOCOMMUNICATION SYSTEM USING GEOSTATIONARY AND NON-GEOSTATIONARY SATELLITES

(57) Abstract

A radiocommunication system and method using a combination of a geostationary (GEO) and a plurality of medium earth orbit (MEO) satellites are disclosed. First, a GEO satellite is launched to provide initial system capacity. Next, MEO satellites are successively launched into positions where they can supplement the coverage of the GEO satellite during peak traffic hours. Finally, when a sufficient number of MEO satellites are in place, the GEO satellite can provide the supplementary capacity.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

RADIOCOMMUNICATION SYSTEM USING GEOSTATIONARY AND NON-GEOSTATIONARY SATELLITES

BACKGROUND

5 The present invention generally relates to methods and systems for providing radiocommunications and, more particularly, to such methods and systems which use satellites to provide radiocommunications.

 In the past, satellite systems for providing global coverage have been of one of three types, broadly classifiable by orbiting distance into geostationary
10 (GEO), low earth orbit (LEO) and medium earth orbit (MEO). An example of a geostationary satellite communications system is the INMARSAT system (International Maritime Satellite Organization). One advantage of geostationary satellites is that they remain in a fixed position relative to the earth, and only four such satellites are required to illuminate the entire earth. A disadvantage of
15 geostationary satellites is that they are very distant, needing high transmit power and large antennas to provide communications capacity and incurring about a 1/4 second, round-trip, signal propagation delay.

 An example of a LEO system is the IRIDIUM system proposed by Motorola. An advantage of LEO systems is that the satellites are much closer to
20 the earth, thereby providing improved communications. Since the satellites are closer to the earth, less transmitting power is needed for both the satellite and an individual user's transceiver. A disadvantage is that about 70 satellites are required to give 24 hour coverage to most points on the globe. Moreover, satellites in low earth orbits move quite rapidly relative to the earth, thereby
25 causing high Doppler shifts and frequent handovers of communication from one satellite to the next.

 An example of the compromise MEO system is the ODYSSEY satellite system proposed by TRW. The orbital altitude of MEO satellites lies between the GEO and MEO orbits, providing better communication quality than a GEO
30 system, with less movement and Doppler shift than an LEO system. Moreover, MEO systems provide more or less 24 hour coverage to most points on the globe

using between 8 and 18 satellites which is much less expensive than the about 70 satellite LEO solution.

While the MEO solution represents a good compromise between conflicting requirements, it suffers from a practical disadvantage that almost all
5 satellites must be in place before coverage is sufficient (in percentage of time available) to be considered attractive to subscribers. This lesson was learned from the GPS satellite navigation system, which is also a MEO solution. Thus, a considerable investment spanning a multi-year program is needed before significant revenue can be expected when implementing a MEO system.

10 Accordingly, it would be desirable to provide radiocommunication systems and methods which overcome the foregoing drawbacks of conventional LEO, MEO and GEO solutions.

SUMMARY

15 According to exemplary embodiments of the present invention a hybrid GEO/MEO solution begins life with the launch of a geostationary satellite that provides radiocommunication coverage to a region of major expected traffic growth, but has a limited capacity which is sufficient to support only an initial number of subscribers. This is followed by the successive launch of a number of
20 MEO satellites. The MEO satellites can, initially, supplement the coverage of the geostationary satellite. Later, once sufficient MEO satellites are in orbit, the primary traffic burden can be relegated to the MEO satellites, with the GEO satellite performing a supplementary role. Finally, if desired, enough MEO satellites can be launched to provide all of the desired system capacity.

25 In this way, a major drawback of MEO systems, specifically the lengthy period between initial launching and sufficient capacity to reach profitability, is overcome since systems according to the present invention provide instant capacity by first launching a geostationary satellite.

BRIEF DESCRIPTION OF THE DRAWINGS

The foregoing, and other, objects, features and advantages of the present invention will be more readily understood upon reading the following detailed description in conjunction with the drawings in which:

5 Figure 1 illustrates a geostationary satellite orbiting the earth according to the present invention;

 Figure 2 illustrates a geostationary satellite and several medium earth orbit satellites according to another exemplary embodiment of the present invention; and

10 Figure 3 shows a geostationary satellite and many medium earth orbit satellites according to an exemplary embodiment.

DETAILED DESCRIPTION

 According to the present invention, Figure 1 shows a first satellite 10
15 which will be established in a geostationary orbit to provide the initial capacity of the system. Although limited in its capacity, this geostationary satellite 10 can provide sufficient capacity to serve a limited number of subscribers within a predefined geographical coverage or traffic area 20. Thus, for example, if a
20 terminal unit 30 remains within the geographical coverage area 20 and is one of the limited number of subscribers served by geostationary satellite 10, the terminal unit 30 would expect to receive good service except, perhaps, at peak usage times.

 During a second phase of system development, successive satellites 40 can be launched into a medium earth orbit as seen in Figure 2. For example, such
25 an orbit could be a so-called harmonically synchronous orbit whereby the satellite orbits the earth an integral number of times in one sidereal day such that the ground track repeats. For example, an orbital radius of 16756 km (orbital height 10386 km) gives 4 orbits per sidereal day. Note that each of the medium earth orbit satellites 40 could have greater nominal capacity than the geostationary
30 satellite 10 due to their relative proximity. Of course, a single medium earth

desirable to launch the geostationary satellite first to provide instant capacity, one or more medium earth orbit satellites could be launched before the geostationary satellite. Those skilled in the art will readily appreciate that many modifications and adaptations are contemplated by the present invention whose scope is defined
5 by the appended claims including all equivalents thereof.

Claims:

1. A satellite communications system comprising:
at least one geostationary satellite and at least one medium earth orbiting
5 satellite for providing radio communications to a plurality of remote subscriber
terminals, in which the at least one geostationary satellite provides radio
communications to said remote subscriber terminals during periods when the
remote subscriber terminals cannot access one of said at least one medium earth
orbit satellites.
- 10 2. A satellite communications system comprising:
a geostationary satellite which provides radio communication service to a
plurality of remote subscriber terminals until a first medium orbit satellite is
operational, wherein said first medium orbit satellite supplements the radio
15 communication service of said geostationary satellite after the first medium orbit
satellite is operational.
3. A system according to claim 2 wherein said first medium orbit
satellite is disposed in a position to cover at least one peak traffic area at peak
20 times of day.
4. A system according to claim 2 further comprising:
a plurality of additional medium earth orbit satellites which
become operational after said first medium orbit satellite becomes operational,
25 wherein said
geostationary satellite directs its capacity to serve areas determined based on
traffic and service capacity of the medium earth orbit satellites.
5. A system according to claim 1 in which said geostationary satellite
30 is followed successively by an increasing number of medium earth orbit

satellites, said geostationary satellite providing one of: stand alone service to subscribers,
service to subscribers supplemented at peak periods by at least one medium earth orbit satellite, and service for gaps in coverage provided by said medium earth orbit satellites.

6. The system according to claim 5, wherein the service provided by said geostationary satellite is determined based on a number of medium earth orbit satellites in orbit.

10

7. A method of providing radiocommunication to a plurality of terminal units comprising the steps of:
launching a satellite into a geostationary orbit;
providing radiocommunication service to said plurality of terminal units
15 using only said geostationary satellite prior to launching additional satellites;
launching a plurality of satellites into a medium earth orbit; and
providing radiocommunication service using both said geostationary satellite and at least one of said plurality of medium earth orbit satellites.

20 8. The method of claim 7 wherein said second providing step further comprises the steps of:

providing radiocommunication service using said at least one of said plurality medium earth orbit satellites to supplement said service of said geostationary satellite until a predetermined number of said medium earth orbit
25 satellites have been launched, after which providing radiocommunication service using said geostationary satellite to supplement service of said medium earth orbit satellites.

9. A satellite communications system for serving a number of
30 ground-base terminals with varying activity levels comprising:

a geostationary satellite disposed so as to be visible from the service area
24 hours a day;

at least one sub-synchronous satellite in an orbit having a repeating
ground track timed to cover said service area at times of expected peak activity
5 of said ground-based terminals.

10. The communications system of claim 9 further comprising a
central ground station in communication with said geostationary satellite and with
said sub-synchronous satellite when visible for relaying signals between the
10 public switches' telephone and said terminals via at least one of said satellites.

11. The communications system of claim 10 further comprising control
means to steer antenna spot beams of said geostationary satellite to locations
momentarily not adequately served by said at least one sub-synchronous satellite.
15

12. The communications system of claim 11 in which said control
means is a beamforming computer.

13. The communications system of claim 12 in which said
20 beamforming computer is located at said central station.

14. A communications system for providing telephone communications
between portable wireless terminals and the public switched telephone system via
orbiting satellites comprising:

25 at least one geostationary relay satellite comprising an electronically
steerable antenna;

at least one sub-synchronous relay satellite;

a tracking network for tracking the instantaneous position of said satellite
and feeding information to communications gateway stations;

at least one communications gateway station connected to the PSTN and in communication with said at least one geostationary relay satellite, said gateway station comprising:

- control means for controlling the areas illuminated by said
- 5 steerable antenna's beams;
- routing means for routing signals between said portable terminals and the PSTN via a satellite and antenna beam controlled based on information from said tracking network.

1 / 2

Fig. 1





Fig. 2

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

INTERNATIONAL SEARCH REPORT

Inter national Application No

PCT/US 95/07837

A. CLASSIFICATION OF SUBJECT MATTER
 IPC 6 H04B7/195 H04B7/19

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 H04B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP,A,0 233 563 (ERNO) 26 August 1987 see claims ---	1-14
X	WO,A,88 04866 (MESSERSCHMITT-BÖLKOW-BLOHM) 30 June 1988 see claims; figure 1 ---	1-14
Y	EP,A,0 017 597 (SNIAS) 15 October 1980 see claims ---	1-14
Y	US,A,4 809 935 (DRAIM) 7 March 1989 see column 2, line 14 - line 40 ---	1-14
A	EP,A,0 507 688 (ALCATEL ESPACE) 7 October 1992 see page 3, line 37 - page 4, line 1 --- -/--	9-13



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

A document member of the same patent family

Date of the actual completion of the international search

24 October 1995

Date of mailing of the international search report

15.12.95

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
 NL - 2280 HV Rijswijk
 Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
 Fax (+31-70) 340-3016

Authorized officer

Bischof, J-L

INTERNATIONAL SEARCH REPORT

Inter. Application No
PCT/US 95/07837

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	<p>EP,A,0 536 921 (SPACE SYSTEMS/LORAL INC.) 14 April 1993 see column 5, line 50 - column 7, line 12; figure 1</p> <p style="text-align: center;">-----</p>	14

A diagram illustrating a geostationary satellite system. At the center is a circle labeled "EARTH". A small antenna symbol, labeled 30, is positioned on the Earth's surface. Surrounding the Earth is a circular orbit. Three satellites, each labeled 40, are positioned on this orbit. Each satellite consists of a rectangular body with two circular antennas extending from it. Dashed lines connect the Earth's surface antenna (30) to the three satellites (40). A large outer circle, labeled 20, represents the coverage area or a larger orbit. A rectangular box, labeled 10, is positioned at the top of the diagram, connected by dashed lines to the three satellites (40), indicating a ground station or a network of stations.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

INTERNATIONAL SEARCH REPORT

Inter national Application No

PCT/US 95/07837

A. CLASSIFICATION OF SUBJECT MATTER
 IPC 6 H04B7/195 H04B7/19

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
 IPC 6 H04B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP,A,0 233 563 (ERNO) 26 August 1987 see claims ---	1-14
X	WO,A,88 04866 (MESSERSCHMITT-BÖLKOW-BLOHM) 30 June 1988 see claims; figure 1 ---	1-14
Y	EP,A,0 017 597 (SNIAS) 15 October 1980 see claims ---	1-14
Y	US,A,4 809 935 (DRAIM) 7 March 1989 see column 2, line 14 - line 40 ---	1-14
A	EP,A,0 507 688 (ALCATEL ESPACE) 7 October 1992 see page 3, line 37 - page 4, line 1 --- -/--	9-13

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

A document member of the same patent family

Date of the actual completion of the international search

24 October 1995

Date of mailing of the international search report

15.12.95

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
 NL - 2280 HV Rijswijk
 Tel. (+31-70) 340-2040, Tx. 31 651 epo nl.
 Fax (+31-70) 340-3016

Authorized officer

Bischof, J-L

INTERNATIONAL SEARCH REPORT

Inter national Application No
PCT/US 95/07837

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	<p>EP,A,0 536 921 (SPACE SYSTEMS/LORAL INC.) 14 April 1993 see column 5, line 50 - column 7, line 12; figure 1</p> <p>-----</p>	14

INTERNATIONAL SEARCH REPORT

Information on patent family members

Inter national Application No

PCT/US 95/07837

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP-A-0233563	26-08-87	DE-A- 3605096 JP-A- 62193421	20-08-87 25-08-87
WO-A-8804866	30-06-88	DE-A- 3644176 AU-B- 607738 AU-B- 1152388 EP-A- 0295295 US-A- 4985706	14-07-88 14-03-91 15-07-88 21-12-88 15-01-91
EP-A-0017597	15-10-80	FR-A- 2453780 AT-T- 5182 JP-A- 55160877	07-11-80 15-11-83 15-12-80
US-A-4809935	07-03-89	NONE	
EP-A-0507688	07-10-92	FR-A- 2674997 JP-A- 5110485 US-A- 5248980	09-10-92 30-04-93 28-09-93
EP-A-0536921	14-04-93	AU-B- 1021595 AU-B- 1021695 AU-B- 657365 AU-A- 2628392 CA-A- 2078932 JP-A- 5292015 US-A- 5448623	16-03-95 16-03-95 09-03-95 22-04-93 11-04-93 05-11-93 05-09-95

THIS PAGE BLANK (USPTO)

THIS PAGE BLANK (USPTO)